

A close-up photograph of a person's hand peeling a blue protective film from a metallic surface. The hand is wearing a black, perforated wristband. The film is being lifted at an angle, revealing the reflective metal underneath. The background is a light-colored, possibly white, surface.

prestotape

METAL PROTECTION FILMS

www.prestotape.com
(800) 331-1373

USA Manufacturer of specialty
tapes, temporary surface protection
films, and print wall media.



NEW HIGH PERFORMANCE METAL PROTECTION FILMS

15HP60 Medium Tack Metal Film

Co-extruded medium adhesion protective film designed for a variety of surface protection applications

Specific Surface Applications Include:

- General: Smooth Semi-Gloss Natural Stone & Synthetic, High Pressure Laminates
- Metals: 304, 416 Finish Stainless Steel, Aluminum, General Metals (Painted, Powder Coated, Non-Painted)
- Painted: Smooth Satin-Gloss, Lightly Textured Semi/High-Gloss
- Plastics: Smooth Satin-Gloss, Lightly Textured Semi/High-Gloss

Process Use: Die Cutting (Rotary, Flatbed), Punching, Sheering, Fabricating (Soft to Hard Bends), Slitting, Forming

Thickness: 1.5 mil // Adhesion To Steel: 7 oz/in // Usage: Temporary Protection Up To 6 Months

15HP40 Low Tack Metal Film

Co-extruded low adhesion protective film designed for a variety of surface protection applications

Specific Surface Applications Include:

- General: Smooth Semi-Gloss Natural Stone & Synthetic, High Pressure Laminates
- Metals: Coarse Abrasive # 3, General Purpose Polished #4 Stainless Finish, 304, 416 Stainless Steel, Aluminum, General Metals (Painted, Powder Coated, Non-Painted)
- Painted: Smooth Semi-Gloss/Satin-Gloss, Lightly Textured Semi/High-Gloss
- Plastics: Smooth Semi-Gloss
- Process Use: Die Cutting (Rotary, Flatbed), Punching, Sheering, Fabricating (Soft to Hard Bends), Slitting, Forming

Thickness: 1.5 mil // Adhesion To Steel: 4 oz/in // Usage: Temporary Protection Up To 6 Months

15HP20 Extra Low Tack Metal Film

Co-extruded ultra low adhesion protective film designed for a variety of surface protection applications

Specific Surface Applications include:

- General: High-Gloss Laminates, LCD Screens, Polycarbonate, Glass
- Metals: High Polished #7, Mirror Finish #8 Stainless Steel
- Painted: Smooth High Gloss, Mirror Gloss Painted, or Non-Painted Surfaces
- Plastics: Smooth High Gloss, Mirror Gloss Painted, or Non-Painted Surfaces
- Process Use: Die Cutting (Rotary, Flatbed), Punching, Sheering, Fabricating (Soft to Hard Bends), Slitting, Forming
- Thickness: 1.5 mil // Adhesion to Steel: 2 oz/in // Usage: Temporary Protection Up To 6 Months

20HP60 Medium Tack Metal Film

Co-extruded medium adhesion protective film designed for a variety of surface protection applications

Specific Surface Applications include:

- General: Smooth Semi-Gloss Natural Stone & Synthetic, High Pressure Laminates
- Metals: 304, 416 Finish Stainless Steel, Aluminum, General Metals (Painted, Powder Coated, Non-Painted)
- Painted: Smooth Satin-Gloss, Lightly Textured Semi/High-Gloss
- Plastics: Smooth Satin-Gloss, Lightly Textured Semi/High-Gloss
- Process Use: Die Cutting (Rotary, Flatbed), Punching, Sheering, Fabricating (Soft to Hard Bends), Slitting, Forming

Thickness: 2 mil // Adhesion to Steel: 7 oz/in

Usage: Temporary Protection Up To 6 Months



**all films available
in blue or clear,
with 6-month
UVI additive**

20HP40 Low Tack Metal Film

Co-extruded low adhesion protective film designed for a variety of surface protection applications

Specific Surface Applications include:

- General: Smooth Semi-gloss Natural Stone & Synthetic, High Pressure Laminates.
- Metals: Coarse Abrasive # 3, General Purpose Polished #4 Stainless Finish, 304, 416 Stainless Steel, Aluminum, Painted, Powder Coated, Non-Painted General Metals
- Painted: Smooth Semi-Gloss, Satin-Gloss, Lightly Textured Semi/High-Gloss
- Plastics: Smooth Semi-Gloss
- Process Use: Die Cutting (Rotary, Flatbed), Punching, Sheering, Fabricating (Soft to Hard Bends), Slitting, Forming

Thickness: 2 mil // Adhesion to Steel: 4 oz/in // Usage: Temporary Protection Up To 6 Months

20HP20 Extra Low Tack Metal Film

Co-extruded ultra low adhesion protective film designed for a variety of surface protection applications

Specific Surface Applications include:

- General: High-Gloss Laminates, LCD Screens, Polycarbonate, Glass
- Metals: High Polished #7, Mirror Finish #8 Stainless Steel
- Painted: Smooth High Gloss, Mirror Gloss Painted, or Non-Painted Surfaces
- Plastics: Smooth High Gloss, Mirror Gloss Painted, or Non-Painted Surfaces
- Process Use: Die Cutting (Rotary, Flatbed), Punching, Sheering, Fabricating (Soft to Hard Bends), Slitting, Forming

Thickness: 2 mil // Adhesion to Steel: 2 oz/in // Usage: Temporary Protection Up To 6 Months

25HP60 Medium Tack Metal Film

Co-extruded medium adhesion protective film designed for a variety of surface protection applications

Specific Surface Applications include:

- General: Smooth Semi-Gloss Natural Stone & Synthetic, High Pressure Laminates
- Metals: 304, 416 Finish Stainless Steel, Aluminum, General Metals (Painted, Powder Coated, Non-Painted)
- Painted: Smooth Satin-Gloss, Lightly Textured Semi/High-Gloss
- Plastics: Smooth Satin-Gloss, Lightly Textured Semi/High-Gloss
- Process Use: Die Cutting (Rotary, Flatbed), Punching, Sheering, Fabricating (Soft to Hard Bends), Slitting, Forming

Thickness: 2.5 mil // Adhesion To Steel: 7 oz/in // Usage: Temporary Protection Up To 6 Months

25HP40 Low Tack Metal Film

Co-extruded low adhesion protective film designed for a variety of surface protection applications

Specific Surface Applications include:

- General: Smooth Semi-Gloss Natural Stone & Synthetic, High Pressure Laminates.
- Metals: Coarse Abrasive # 3, General Purpose Polished #4 Stainless Finish, 304, 416 Stainless Steel, Aluminum, General Metals (Painted, Powder Coated, Non-Painted)
- Painted: Smooth Semi-Gloss, Satin-Gloss, Lightly Textured Semi/High-Gloss
- Plastics: Smooth Semi-Gloss
- Process Use: Die Cutting (Rotary, Flatbed), Punching, Sheering, Fabricating (Soft to Hard Bends), Slitting, Forming

Thickness: 2.5 mil // Adhesion to Steel: 4 oz/in // Usage: Temporary Protection Up To 6 Months

25HP20 Extra Low Tack Metal Film

Co-extruded ultra low adhesion protective film designed for a variety of surface protection applications

Specific Surface Applications include:

- General: High-Gloss Laminates, LCD Screens, Polycarbonate, Glass
- Metals: High Polished #7, Mirror Finish #8 Stainless Steel
- Painted: Smooth High Gloss, Mirror Gloss Painted, or Non-Painted Surfaces
- Plastics: Smooth High Gloss, Mirror Gloss Painted, or Non-Painted Surfaces
- Process Use: Die Cutting (Rotary, Flatbed), Punching, Sheering, Fabricating (Soft to Hard Bends), Slitting, Forming

Thickness: 2.5 mil // Adhesion to Steel: 2 oz/in // Usage: Temporary Protection Up To 6 Months

NEW TEXTURED METAL FILMS

309636 Super High Tack Textured Metal Film

Ideal for Heavy Textured Metals: Non- Painted, Painted & Powder Coated

Specific Surface Applications include:

- Metals: Rough To Heavy Textured Metals Including Hammered, Fluted, Traction Tread, Diamond, Quilted
- Painted Metal: Hard To Stick To Paints
- Plastics: Rough To Heavy Textured Plastics and Fiberglass Surfaces
- Process Use: Light Fabrication, Protection, Embossing
- Not Compatible With: High Surface Energy Substrates

Thickness: 3 mil // Adhesion To Steel: 36 oz/in // Usage: Temporary Protection Up To 6 Months

309432 Extra High Tack Textured Metal Film

Ideal for Medium to Heavy Textured Metals: Non- Painted, Painted & Powder Coated

Specific Surface Applications include:

- Metals: Rough To Medium Textured Metals Including Hammered, Fluted, Traction Tread, Diamond, Quilted
- Painted Metal: Hard To Stick To Paints
- Plastics: Rough To Medium Textured Plastics and Fiberglass Surfaces
- Process Use: Light Fabrication, Protection, Embossing
- Not Compatible With: High Surface Energy Substrates

Thickness: 3 mil // Adhesion To Steel: 32 oz/in // Usage: Temporary Protection Up To 6 Months

309230 High Tack Textured Metal Film

Ideal for Light to Medium Textured Metals: Non- Painted, Painted & Powder Coated

Specific Surface Applications include:

- Metals: Rough To Low Textured Metals Including Hammered, Fluted, Traction Tread, Diamond, Quilted
- Painted Metal: Hard To Stick To Paints
- Plastics: Rough To Low Textured Plastics and Fiberglass Surfaces
- Process Use: Light Fabrication, Protection, Embossing
- Not Compatible With: High Surface Energy Substrates

Thickness: 3 mil // Adhesion To Steel: 26 oz/in // Usage: Temporary Protection Up To 6 Months

PRESTO TAPE

Bensalem, PA

800-331-1373

info@prestotape.com

GET IN TOUCH

Our team is available to help find the right product for your business. We have an extensive catalog of products in multiple tack levels, colors, sizes, and mil thickness.



P R E S T O T A P E . C O M