



NEW HIGH PERFORMANCE METAL PROTECTION FILMS

A HOW-TO GUIDE TO CHOOSING

all films available in blue or clear, with 6-month UVI additive



IDEAL INDUSTRIES & APPLICATIONS



RECOMMENDED SURFACES



TYPICAL FABRICATION PROCESSES

	HIGH TACK Adhesion: High Adhesion Pull: 7oz/in	MEDIUM TACK Adhesion: Medium Adhesion Pull: 4oz/in	LOW TACK Adhesion: Low Adhesion Pull: 2oz/in
Metal Roofing & Building Products	✓	✓	
Coil Coating Operations	✓		
Roll Forming Facilities	✓		
Construction Products	✓		
Agricultural Equipment	✓		
Heavy Equipment Components	✓		
Transportation & Trailer Manufacturing	✓		
Architectural Panels		✓	
HVAC Manufacturing		✓	
Metal Service Centers		✓	
Trailer Manufacturing		✓	
Aluminum Fabrication		✓	
Sheet Metal Fabrication		✓	
Stainless Steel Fabrication			✓
Appliance Manufacturing			✓
Elevator Panels			✓
Architectural Metals			✓
Decorative Metal Components			✓
Sign Manufacturing			✓
Display Fixtures			✓
304 Stainless Steel	✓	✓	
416 Finish Stainless Steel	✓	✓	
Aluminum	✓	✓	
Painted Metals	✓	✓	
Powder-Coated Metals	✓	✓	
Textured & Rough Metal Surfaces	✓		
#3 Coarse Abrasive Stainless Steel		✓	
#7 Polished Stainless Steel		✓	✓
#8 Mirror Finish Stainless Steel			✓
Other Highly Polished Metal Surfaces			✓
Die Cutting (Rotary & Flatbed)	✓	✓	✓
Punching	✓	✓	✓
Shearing	✓	✓	✓
Slitting	✓	✓	✓
Forming	✓	✓	✓
Soft to Hard Bends	✓	✓	✓

NEW TEXTURED METAL FILMS

309636 HIGH TACK TEXTURED METAL FILM

Ideal for Heavy Textured Metals: Non- Painted, Painted & Powder Coated

- Light Fabrication, Protection, Embossing
 - Not Compatible With High Surface Energy Substrates
- Thickness: 3 mil • Adhesion To Steel: 36 oz/in • Temporary Protection Up To 6 Months

309432 MEDIUM TACK TEXTURED METAL FILM

Ideal for Medium to Heavy Textured Metals: Non- Painted, Painted & Powder Coated

- Process Use: Light Fabrication, Protection, Embossing
 - Not Compatible With: High Surface Energy Substrates
- Thickness: 3 mil • Adhesion To Steel: 32 oz/in • Temporary Protection Up To 6 Months

309230 LOW TACK TEXTURED METAL FILM

Ideal for Light to Medium Textured Metals: Non- Painted, Painted & Powder Coated

- Process Use: Light Fabrication, Protection, Embossing
 - Not Compatible With: High Surface Energy Substrates
- Thickness: 3 mil • Adhesion To Steel: 26 oz/in • Temporary Protection Up To 6 Months

CONTACT US

www.prestotape.com

(800) 331-1373

INFO@PRESTOTAPE.COM